

Urochem 107

EPOXY SPECIALISED PRIMER

DESCRIPTION

Urochem 107 is a two-part moisture tolerant primer that has a long open time and offers improved adhesion to substrates with minimal oil contamination.

PRODUCT APPLICATION

- Its main application is as a primer coat for use with Urochem polyurethane and epoxy compounds where the substrate is damp or has mild oil contamination.
- Please consult technical department before use.

SURFACE PREPARATION

- Ensure all surfaces to be primed are clean, sound, and free of standing water. Laitance or surface contamination should be removed by thorough wire brushing, surface grinding or grit blasting.
- Vacuum or blow with compressed air to ensure thorough removal of dirt.

APPLICATION

- Mix the base and activator together thoroughly. Brush or roller apply a thin coat of primer and allow to dry.
- ***If not overcoated within three hours, reprime.***

CLEANING

Clean brushes after use with **Urochem 901**.

SAFETY

- Contains organic solvents
- Flammable.
- Do not use in confined spaces. Ensure adequate ventilation and the absence of any ignition source. Wear protective clothing. In case of eye contact wash well with water and obtain medical advice.



Urochem Trading (Pty) Ltd

Unit XP2, AEL Industrial complex, Cnr Ecqip and Weighbridge
Modderfontein, Gauteng; 1645

(+27) 11 608 2073 • www.urochem.co.za

Urochem 107

EPOXY SPECIALISED PRIMER

TYPICAL PROPERTIES

Mixing Ratio	Twin pack
Pot Life	30 min
Practical Cure	2 Hrs @ 25° C
Full Cure	24 Hrs
Colour	Light Brown
Density	0,97
Theoretical coverage	8 - 10 m ² / Lt
Shelf Life	12 Months
Application Temp.	5 - 35°C
Service Temp.	-25 - 90°C
Pack Size	500ml
Cleaning	Urochem 901
Storage	Store in a cool dry place

The information supplied is believed to be reliable. As we do not have any control over the processing or application of the product, we cannot guarantee the results to be obtained. Users assume all risks and liability resulting from the use of this product and must confirm the suitability thereof by conducting their own tests. No guarantee is expressed or implied. Liability is limited to replacement of faulty material. Field service provided does not constitute supervisory responsibility.

FOR PROFESSIONAL USE ONLY



Urochem Trading (Pty) Ltd

Unit XP2, AEL Industrial complex, Cnr Ecqip and Weighbridge
Modderfontein, Gauteng; 1645

(+27) 11 608 2073 • www.urochem.co.za